

INTERNATIONAL MELGES 24 CLASS ASSOCIATION



The following amendments to the Class Rules have been approved to be effective 16th December 2009.

Rule A.9.2

Amendment: Add second sentence to read as follows:
"ISAF plaques were issued from sail number 350 onwards."

Rule A.10.1

Amendment: Add second sentence to read as follows:
"Boats with sail numbers prior to 350 shall carry the number as issued by Melges Performance Boatworks."

Rule A.11.1

Amendment: Delete the first sentence and replace with the following:
"A **certificate** issued after March 2009 shall record the following information:"

Rule C.7.2 (a) (2)

Amendment: Delete "sheave height from the fixing point and" from the first sentence so it now reads as follows:
"The manufacturer or brand of the blocks and winches is optional. The sheave diameter shall not exceed the following dimensions:

	Minimum	Maximum.
Jib clew blocks. Diameter:	26mm.	30mm.
Jib car blocks. Diameter:	30mm.	46mm.
Jib ratchet blocks. Diameter:	54mm.	78mm.
Mainsheet track block. Diameter:	48mm.	58mm.
Mainsheet boom blocks. Diameter:	48mm.	58mm.
Mainsheet ratchet block. Diameter:	54mm.	78mm.
Spinnaker turning blocks. Diameter:	48mm.	78mm.
Spinnaker deck ratchet blocks. Dia:	54mm.	78mm.
Bowsprit end block. Diameter:	Optional	
All control line blocks. Diameter:	Optional	
Hiking line block. Diameter:	Optional.	

The spinnaker tack line cleat may be changed to a stopper."

INTERNATIONAL MELGES 24 CLASS ASSOCIATION



Rule C.7.2 (a) (15)

Amendment: Add second sentence to the end of the rule to read as follows:
“To protect the spinnaker, a deflector or similar device of optional design may be installed totally within a 300mm radius of the forward most point of the hiking lines.”

Rule D.2.5 (a)

Amendment: Delete the current rule and replace with the following:
“Hulls from sail number 350 onwards shall carry the ISAF plaque permanently placed on the starboard side, aft face of the transom.”
